Compact Track Loaders / T590 Compact Track Loader

Specifications & Options

Standard O	otional Not Applicable		Units		
		Bol	bcat T590		
Configuration		Standard	Roller Suspension Option		
Engine					
Emissions Tier (EPA)	Tier 4	Tier 4		
Engine Cooling			Liquid		
Engine Fuel			Diesel		
Horsepower			66 hp		
Turbocharged Engin	e				
Performan	ce				
Rated Operating Cap	pacity (SAE)	2,100 lb	1,950 lb		
Operating Capacity	(50% of Tip)	3000 lb	2786 lb		
Tipping Load		6000 lb	5571 lb		
Operating Weight		7822 lb	8007 lb		
Travel Speed		7.1 mph	7.1 mph		
Travel Speed (2-spe		10.4 mph	10.4 mph		
Ground Pressure (R	ubber)	5.1 psi	5.2 psi		
Capacities					
Fuel Tank		36.5 gal	24.8 gal		
Hydraulic S	System				
System Relief @ Qu	ck Couplers	3,	3,500 psi		
Auxiliary Std Flow		17.	17.1 gal/min		
Auxiliary High Flow		26.	26.7 gal/min		

Dimension

Length		133 in	
Length without Attachment		104.6 in	
Length with Standard Bucket		133 in	
Width	67.1 in		71.5 in
Height		77.8 in	
Height with Operator Cab		77.8 in	
Height to Bucket Hinge Pin		119 in	
Reach @ Maximum Height		34.9 in	
Turning Radius	80 in		80 in
Length of track on ground		54.1 in	
Track Width		12.6 in	
Track Width - Optional		15.8 in	

Features

Joystick Control

Air Conditioning

Backup Alarm

BICS System (Interlock)

Cab Heater

Operating Lights

Suspension Seat

Two Speed Travel

Deluxe Instrumentation

Engine Shutdown

Hydraulic Bucket Positioning

High Flow Option

Auxiliary Hydraulics

Bob-Tach Attachment System

Power Bob-Tach

ACS (Switchable Controls)

Ride Control

Horn

Certain specification(s) are based on engineering calculations and are not actual measurements. Specification(s) are provided for comparison purposes only and are subject to change without notice. Specification(s) for your individual equipment will vary based on normal variations in design, manufacturing, operating conditions, and other factors.